


TECHNICAL DATA SHEET - DESCRIPTION		
RANGE	COLLECTION	NUMBER
 ACOUSTIC	EOS Color 2	FT N° 77/V2

This acoustic wallcovering combines the technical qualities of a high performance acoustic backing and the nobility of a warm faux-suede, alpha w 0.30 / NRC 0.40. Fast and easy hanging, it is delivered with a transparent film that protects the fabric from building site storage conditions. According to the regulation, this wallcovering gets an efficient fire classification B s2 d0.

Description

Item code	EOSC 9104...
Name	EOS Color 2
Range	Acoustic 0.3
Type	Acoustic textile wallcovering
Plain	19 colours
Patterned	No

Composition

Type	Polyester faux-suede
Backing	Polyurethane acoustic foam
Weight	350 g/m ²
Thickness	5/6 mm
Treatment	Waterproof surface

Regulations - Environment

Fire rating	B s2 d0 / Class A	Standard EN 13 501 -1 / ASTM E- 84
Acoustics	Alpha w 0.30 / NRC 0.40	Standard EN 20 354 / AS ISO 354-2006
Light fastness	≥ 5	Standard EN 259
Thermal resistance	R = 0,12 m ² .K/W	Standard EN 12 667
VOCs	A+	ISO 16000
CE marking	DOP-CPR-EOSNMD-59	Standard EN 15 102
Care	Wipeable	Standard EN 259
Use	Normal	Standard EN 259

Packing - Packaging

Size of widths	140 cm (+/- 3%)	
Length of roll	25 lm, 15 lm, 10 lm	
Partial sale to order	No	
Dispenser box	Yes	FSC Certified Cardboard
Suspended core packaging	Yes	
Box size	1530 X 480 X 490 mm for 25 lm and 15 lm	
Weight of a roll	15,00 Kg for 25 lm, 9 Kg for 15 lm (+/- 10%)	

Hanging operation

Adhesive	Ovalit TM - Ovalit F (Metylan - Henkel)
Adhesive instructions	Apply to the wall, using a roller
Quantity of adhesive	250 - 450 gr/m ²
Match	Free match
Hanging direction	Straight strips
Seams	Edge to edge / butt seam
Removal	Dampen before stripping
For partitions	Yes - 140cm width