


TECHNICAL DATA SHEET - DESCRIPTION		
RANGE	COLLECTION	NUMBER
 ACOUSTIC	SIGNATURE Wood	FT N° 70

This acoustic wallcovering combines the technical qualities of a high performance acoustic backing and the nobility of a warm Jersey fabric, NRC 0,30. Fast and easy hanging. According to the regulation, this wallcovering gets an efficient fire classification Class A.

Description

Item code	SIGW 9142 / 9143 / 9144
Name	SIGNATURE Wood
Range	Acoustic 0.3
Type	Acoustic textile wallcovering
Plain	2 wood species / 15 colours
Patterned	1 marquetry pattern / 3 colours

Composition

Type	Transfer printed Jersey fabric on acoustic backing
Backing	Polyurethane acoustic foam
Weight	320 g/m ²
Thickness	.+/- 5 mm

Regulations - Environment

Fire rating	B s1 d0 / Class A	Standard EN 13 501 -1 / ASTM E - 84
Acoustics	Alpha w = 0.25 / NRC 0.30	NF EN ISO 354 / AS ISO 354-2006
Light fastness	Very good light fastness 5 - 6	ISO 105
VOCs	A+	ISO 16000
CE marking	CPR - SIGMD - 58 / www.texdecor.com	Standard EN 15 102
Care	Washable / colour fastness to washing 4 - 5	ISO 105

Packing - Packaging

Size of widths	1,40 lm (+/- 3%)	
Length of roll	30 lm, 20 lm, 10 lm	
Partial sale to order	No	
Dispenser box	Yes	FSC Certified Cardboard
Suspended core packaging	Yes	
Box size	153 X 48 X 49 cm for 30, 20, 10 lm	
Weight of a roll	16 Kg for 30 lm (+/- 10%)	

Hanging operation

Adhesive	Ovalit TM - Ovalit F (Metylan - Henkel)
Adhesive instructions	Apply to the wall, using a roller
Quantity of adhesive	250-450 gr/m ²
Match	Free match for plains / offset match of 70 cm for the pattern
Hanging direction	Straight strips
Seams	Edge to edge seams
Removal	Dampen before stripping
For partitions	Yes - 140 cm width