

## Product technical specification sheet

### Acoustic textile wallcovering - SOFT

---

#### Description

SOFT is an acoustic textile wallcovering made of printed Trevira CS fleece, that improve acoustic comfort : alpha w 0.15 / NRC 0.10. This wallcovering is especially made to be used in community facilities, offices, functional premises: it is shock resistant and washable. In accordance with the regulations this wallcovering has been classified with flame retardancy test Euroclassification B s1 d0. Soft wallcovering is both easy and fast to install: past the wall and butted seam.

Item code	SOFT...
Name	SOFT
Range	ACOUSTIC
Type	Acoustic textile wallcovering
Plain	2 designs - 22 colours

---

#### Composition

Type	Acrylic and polyurethan printed fleece
Backing	Polyester Trevira CS fleece - 200 g/m <sup>2</sup>
Weight	380 g/m <sup>2</sup>
Thickness	1,5 mm +/-

---

#### Regulations - Environment

Fire rating	B s1 d0	Standard EN 13 501 -1
Acoustics	Alpha w 0.15 / NRC 0.10	Standard EN 20 354 / ASTM-C423-90a
Light fastness	≥ 5 (1-8)	Standard EN 259
VOCs	A+	ISO 16000
CE marking	DOP-CPR-LOIR-31	Standard EN 15 102
Care	Washable	Standard EN 259

---

#### Packing - Packaging

Size of widths	95 cm +/- 3cm
Length of rolls	50 lm
Partial sale to order	Yes
Box size	35 x 35 x 107 cm for 50 lm
Weight of a roll	20 kg for 50 lm

---

#### Installation

Adhesive	Ovalit TM (Metylan - Henkel)
Adhesive instructions	Apply to the wall, using a roller
Quantity of adhesive	250 gr/m <sup>2</sup>
Match	Free match
Hanging direction	Reverse hang
Seams	Butted seam
Removal	Strippable
Hanging instructions	<a href="http://www.texdecor.com">www.texdecor.com</a>